Product data sheet
Characteristics

P6W
APC Essential SurgeArrest 6 Outlet Wall Mount, 120V

Purchase

Purchase	P6W

Overview

Model Name	APC Essential SurgeArrest 6 Outlet Wall Mount, 120V
Includes	User Manual,Warranty card
Standard Lead Time	Usually in Stock
Product Distribution	Anguilla,Aruba,Bahamas,Barbados,Belize,Bermuda,Brazil,Canada,Colombia,Costa Rica,Cuba,Dominican Republic,Ecuador,El Salvador,Guatemala,Guyana,Haiti,Honduras,Jamaica,Mexico,Netherlands Antilles,Nicaragua,Panama,Puerto Rico,Trinidad And Tobago,Turks And Caicos Islands,United States,Uruguay,VIRGIN ISLANDS (UNITED STATES)

Output

Number of Outlets	6
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input Power	1200
Input Frequency	50/60 Hz +/- 5 Hz (auto sensing)
Input Connections	NEMA 5-15P
Maximum Line Current per phase	15
Maximum Input Current	15

Surge Protection and Filtering

Surge energy rating	1080
EMI/RFI Noise rejection (100 kHz to 10 mHz)	40
Peak Current Normal Mode	60 (/PH)
Peak Current Common Mode	72
NM Surge Response Time (ns)	1
Let Through Voltage Rating	< 500

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Physical

Net Weight	0.2 kg
Maximum Height	102 mm
Maximum Width	38 mm
Maximum Depth	140 mm
Shipping Weight	0.23 kg
Shipping Height	197 mm
Shipping Width	57 mm
Shipping Depth	241 mm
Master Carton Units	6.0
Master Carton Dimensions (Length x Width x Height)	340 mm x 213 mm x 254 mm
Master Carton Weight	2.08 kg
Color	Beige
Units per Pallet	504.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	ETL
Standard Warranty	Lifetime
Equipment protection policy	Lifetime : $50000
UL 1449 TVSS Rating	400V

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs